



**BREAK AWAY**



## “A Great Start to Long-Lasting Door Solutions!”

Our New Break-Away Bottom Section prevents damage and allows operation when the bottom section of the door is inadvertently hit. **Resets in seconds!**



## FEATURES

- Prevents damage
- Can swing up to 90 degrees inward or outward
- Continued operation once bottom section has been inadvertently hit
- Resets in seconds
- Interior cover prevents damage should section be struck
- Available on all 3000 series, 524 series and 520 series Clopay doors
- Can be retrofit to existing products



Inside View

Clopay's new Break-Away Bottom Section will release from the track and swing up to a full 45° angle inward or outward, preventing further damage to the door. The cable attachment at the bottom of the second section enables the door to continue operating after being struck. The bottom section can be "snapped" back into place in less than a minute. Because the cables are mounted on the second section, doors must be ordered with at least 27" of hi-lift. The bottom section also has a fiberglass sheet on the inside of the section to hide dents if they occur. These sections are available on the 1-3/8" and 2" thick 3000 series doors for both the EPS and the FIP products.

## **SPECIFICATIONS:**

### **Quality assurance:**

Doors shall be insulated or noninsulated steel sectional overhead type as manufactured by Clopay Building Products Co. Each door is provided as one complete unit including sections, brackets, tracks, counterbalance mechanism, and hardware (list options) to suit the opening and headroom available. Door is provided with a break-away bottom section as an integral part of the door, exterior to match door face. Section provided for 2" or 3" rollers and track as required. The interior of the bottom section is lined with fiberglass or 1/8" polycarbonate to prevent damage to the section.

### **Options for break-away bottom section:**

Inside slide lock mechanism provides additional security. Padlock may be applied.

### **Specification requirements:**

Door must have at least 27" of hi-lift; 36" of headroom is required.

Maximum door width: 20'2".

Not compatible with door drop safety device/ bottom brackets.

Not compatible with doors requiring a double torsion shaft. (consult factory)

### **Materials & construction:**

Break-away bottom sections are available on all Clopay Brand 3000 series thermally broken insulated doors, and the 524 and 520 series ribbed steel doors. Section will be provided with flexible neoprene rubber side edges. Bottom astragal retainer and flexible astragal are provided. Interior of section is lined with either fiberglass (3000 series) or 1/8" polycarbonate (500 series).

DISTRIBUTED BY:

